

LISTA DE PRECIOS EN PRODUCTOS  
***HIKVISION***

***27 AGOSTO DE 2015***

# HIKVISION



## 700TVL / 720TVL



**HIKVISION** 700TVL

### DS-2CE55A2N-IRM

700 TVL, Horizontal Resolution, True Day/Night, 2.8/3.6/6mm Fixed Lens, 0.1 lux /F1.2, 20m IR Distance, Wide Operating Temperature Range: -40°C to 60°C(-40°F to +140°F), lens 2.8 / 3.6 / 6 mm.

---



**HIKVISION** 700TVL

### DS-2CE55A2N-IRP

700 TVL Horizontal Resolution, True Day/Night, 2.8/3.6/6mm Fixed Lens, 0.1 lux /F1.2, 20m IR Distance, Wide Operating Temperature Range: -40°C to 60°C(-40°F to +140°F), lens 2.8 / 3.6 / 6 mm.

---



**HIKVISION** 700TVL

### DS-2CS54A1N-IRS

700 TVL, 1/3" DIS, Min. illumination: 0.1 Lux @ F1.2 (0 Lux with IR), True Day/Night, 3-axis (pan/tilt/rotation) positioning, Wide operating temperature range, IP66 rating, 20m IR Distance, OSD Menu

---



**HIKVISION** 700TVL

### DS-2CE55C2N-IRP

700 TVL horizontal resolution, 1/3" DIS, True Day/Night, 2.8 ~ 12mm vari-focal lens, 40m IR distance, Wide operating temperature range.

---



**HIKVISION** 700TVL

### DS-2CE15A2N-IR

700 TVL, 1/3" DIS, 20m IR Distance, ICR, 0.1 Lux/F1.2, 0.3 Lux/F2.2, 12 VDC, Smart IR, Wide operating temperature Range (-40°~60°), IP66, lens 2.8 mm, 3.6 mm & 6 mm.

---



**HIKVISION** 700TVL

### DS-2CE15A2N-VFIR3

700 TVL, • 1/3" DIS, True Day/Night, 700 TVL horizontal resolution, 2.8 ~ 12mm vari-focal lens, 40m IR distance, Wide operating temperature range

---



**HIKVISION** 700TVL

### DS-2CE16A2N-IT1

700 TVL, 700 TVL Horizontal Resolution, True Day/Night, 2.8/3.6/6/8/12/16mm Fixed Lens, 0.1 lux /F1.2, 40m IR Distance, Wide Operating Temperature Range: -40°C to 60°C(-40°F to +140°F)

---



**HIKVISION** 700TVL

### DS-2CE16A2N-IT3

700 TVL, 700 TVL Horizontal Resolution, True Day/Night, 2.8/3.6/6/8/12/16mm Fixed Lens, 0.1 lux /F1.2, 40m IR Distance, Wide Operating Temperature Range: -40°C to 60°C(-40°F to +140°F)

---



**HIKVISION** 700TVL

### DS-2CE16A2N-IT5

700 TVL Horizontal Resolution, True Day/Night, 3.6/6/8/12/16mm Fixed Lens, 0.1 lux /F1.2, 80m IR Distance, Wide Operating Temperature Range: -40°C to 60°C(-40°F to +140°F)

---



**HIKVISION** 700TVL

### DS-2CE55A2N-VFIR3

700 TVL Horizontal Resolution, True Day/Night, 3.6/6/8/12/16mm Fixed Lens, 0.1 lux /F1.2, 80m IR Distance, Wide Operating Temperature Range: -40°C to 60°C(-40°F to +140°F)



## HIKVISION 720TVL

### DS-2CE15C2N-IR

720 TVL, 1/3" PICADIS, Effective Pixels: 1280(H)×960(V), 20m IR Distance, ICR, 0.1 Lux/F1.2, 0.3 Lux/F2.2, 12 VDC, Smart IR, High dynamic range, Wide operating temperature Range (-40°~60°), IP66, lens 2.8 mm, 3.6 mm & 6 mm.

---



## HIKVISION 720TVL

### DS-2CE15C2N-VFIR3

720 TVL Horizontal Resolution, 1/3" PICADIS, True Day/Night, 2.8 ~ 12mm vari-focal lens, 40m IR distance, Smart IR, high dynamic range, Superior video image output and ultra low light illumination, Wide operating temperature range, IP66 Weatherproof

---



## HIKVISION 700TVL

### DS-2CE16C2N-IT1

720 TVL, 1/3" PICADIS, 1.3MP Sensor: 1280 (H) x 960 (V) Effective Pixels, True Day/Night, 720 TVL Horizontal Resolution, 40m IR Distance, Smart IR, IP66 Weatherproof, Wide Operating Temperature Range

---



## HIKVISION 720TVL

### DS-2CE16C2N-IT3

720 TVL, 1/3" PICADIS, 1.3MP Sensor: 1280 (H) x 960 (V) Effective Pixels, True Day/Night, 720 TVL Horizontal Resolution, 80m IR Distance, Smart IR, IP66 Weatherproof, Wide Operating Temperature Range

---



## HIKVISION 720TVL

### DS-2CE16C2N-IT5

720 TVL, 1/3" PICADIS, 1.3MP Sensor: 1280 (H) x 960 (V) Effective Pixels, True Day/Night, 720 TVL Horizontal Resolution, 20m IR Distance, Smart IR, IP66 Weatherproof, Wide Operating Temperature Range

---



## HIKVISION 720TVL

### DS-2CE55C2N-IRM

**720 TVL**, 1/3" PICADIS, 1.3MP Sensor: 1280 (H) x 960 (V) Effective Pixels, True Day/Night, 2.8/3.6/6mm Fixed Lens, 0.1 lux /F1.2, 20m IR Distance, Smart IR, high dynamic range, Superior video image output and ultra low light illumination, Wide operating temperature range, IP66 Weatherproof.

---



## HIKVISION 720TVL

### DS-2CE55C2N-IRP

**720 TVL** Horizontal Resolution, 1/3" PICADIS, 1.3MP Sensor: 1280 (H) x 960 (V) Effective Pixels, True Day/Night, 2.8/3.6/6mm Fixed Lens, 0.1 lux /F1.2, 20m IR Distance, Smart IR, high dynamic range, Superior video image output and ultra low light illumination, Wide operating temperature range, IP66 Weatherproof.

---



## HIKVISION 720TVL

### DS-2CE55C2N-VFIR3

**720 TVL** Horizontal Resolution, 1/3" PICADIS, True Day/Night, 2.8 ~ 12mm vari-focal lens, 40m IR distance, Smart IR, high dynamic range, Superior video image output and ultra low light illumination, Wide operating temperature range, IP66 Weatherproof.

---

# HIKVISION



## TURBO HD 720P / 1080P



**HIKVISION** HD 720P

### DS-2CE56C2T-IR

720 TVL, HD720P Video Output • Adopt HDTVI Technology • True Day/Night • DNR, Smart IR • 20m IR distance • IP66 weatherproof

---



**HIKVISION** HD 720P

### DS-2CE16C2T-IR

HD720P Video Output, Adopt HDTVI Technology, True Day/Night, DNR, Smart IR, 20m IR distance, IP66 weatherproof.

---



**HIKVISION** HD 720P

### DS-2CE16C2T-IT1

HD720P Video Output, Adopt HDTVI Technology, True Day/Night, Smart IR, EXIR technology, 20m IR distance, IP66 weatherproof.

---



**HIKVISION** HD 720P

### DS-2CE16C2T-IT3

HD720P Video Output, Adopt HDTVI Technology, True Day/Night, Smart IR, EXIR technology, 40m IR distance, IP66 weatherproof.

---



**HIKVISION** **HD 720P**

### DS-2CE16C2T-IT5

**HD720P** Video Output, Adopt HDTV Technology, True Day/Night, Smart IR, EXIR technology, 80m IR distance, IP66 weatherproof

---



**HIKVISION** **HD 720P**

### DS-2CE16C5T-VFIR3

**HD720P** Video Output, Adopt HDTV Technology, True Day/Night, 2.8 - 12mm vari-focal lens, OSD menu, 3D DNR, Smart IR, Up to 40m IR distance, Low illumination, Up the Coax(via coaxial cable).

---



**HIKVISION** **HD 720P**

### DS-2CE56D5T-AVPIR3

**HD1080P** Video Output, Adopt HDTV Technology, True Day/Night, 2.8 - 12mm vari-focal lens, OSD menu, 3D DNR, Smart IR, Up to 40m IR distance, IP66 weatherproof & Vandal Proof, Up the Coax(via coaxial cable), 120 dB Wide Dynamic Range

---



**HIKVISION** **HD 720P**

### DS-2CE56C5T-VFIT3

**HD720P** Video Output, Adopt HDTV Technology, True Day/Night, 2.8 - 12mm vari-focal lens, OSD menu, 3D DNR, Smart IR, EXIR technology, 50m IR distance, Low illumination, Up the Coax(via coaxial cable).

---



**HIKVISION** **FULL HD 1080P**

### DS-2CE16D5T-AVFIT3

**HD1080P** Video Output, Adopt HDTV Technology, True Day/Night, 2.8 - 12mm vari-focal lens, OSD menu, 3D DNR, Smart IR, Up to 50m IR distance, Up the Coax(via coaxial cable), 120 dB Wide Dynamic Range



**HIKVISION** FULL HD 1080P

### DS-2CE16D5T-IR

HD1080P Video Output, Adopt HDTVI Technology, True Day/Night, OSD menu, 3D DNR, Smart IR, 20m IR distance, IP66 weatherproof, Up the Coax(via coaxial cable), 120 dB WDR, Lense 6mm.

---



**HIKVISION** FULL HD 1080P

### DS-2CE56D5T-AVPIR3

HD1080P Video Output, Adopt HDTVI Technology, True Day/Night, 2.8 - 12mm vari-focal lens, OSD menu, 3D DNR, Smart IR, Up to 40m IR distance, IP66 weatherproof & Vandal Proof, Up the Coax(via coaxial cable), 120 dB Wide Dynamic Range

---



**HIKVISION** FULL HD 1080P

### DS-2CE56D5T-IRM

HD1080P Video Output, Adopt HDTVI Technology, True Day/Night, OSD menu, 3D DNR, Smart IR, 20m IR distance, IP66 weatherproof, Up the Coax(via coaxial cable), 120 dB Wide Dynamic Range

---



**HIKVISION** FULL HD 1080P

### DS-2CE56D5T-VFIR

HD1080P Video Output, Adopt HDTVI Technology, True Day/Night, 2.8 - 12mm vari-focal lens, OSD menu, 3D DNR, Smart IR, Up to 30m IR distance, Up the Coax, 120 dB Wide Dynamic Range

---





**HIKVISION** 720TVL

### DS-7104HWI-SH

4-ch video & 1-ch audio input, 1 SATA interface, WD1: 25(P) / 30(N) fps/ch, mini 1U case

---



**HIKVISION** 720TVL

### DS-7108HWI-SH

8-ch video & 1-ch audio input, 1 SATA interface, WD1: 25(P) / 30(N) fps/ch, mini 1U case

---



**HIKVISION** 720TVL

### DS-7116HWI-SH

16-ch video & 1-ch audio input, 1 SATA interface, WD1: 25(P) / 30(N) fps/ch, mini 1U case

---



**HIKVISION** 720TVL

### DS-7204HWI-SH

4-ch video & 1-ch audio input, 2 SATA interfaces, WD1: 25(P) / 30(N) fps/ch, 1U case, 19"

---



**HIKVISION** 720TVL

### DS-7208HWI-SH

8-ch video & 1-ch audio input, 2 SATA interfaces, WD1: 25(P) / 30(N) fps/ch, 1U case, 19"

---



**HIKVISION** 720TVL

### DS-7216HWI-SH

16-ch video & 1-ch audio input, 2 SATA interfaces, WD1: 25(P) / 30(N) fps/ch, 1U case, 19"

---

## HIKVISION 720TVL

### DS-7308HWI-SH



H.264 video compression, Up to 32-ch video input , WD1(PAL: 960×576,NTSC:960×480) resolution real-time recording, HDMI and VGA output at up to 1920×1080P resolution, Dual-stream, Gigabit network interfaces, 8ch synchronous playback, HDD quota and group management.

---

## HIKVISION HD 720P

### DS-7208HGHI-SH



H.264 & Dual-stream video compression, Support both HD-TVI and analog cameras with adaptive access, Full channel@720P resolution real-time recording, HDMI and VGA output at up to 1920×1080P resolution, Long transmission distance over coax cable, Support up to 8-ch synchronous playback at 1080P resolution

---

## HIKVISION HD 720P

### DS-7216HGHI-SH



H.264 & Dual-stream video compression, Support both HD-TVI and analog cameras with adaptive access, Full channel@720P resolution real-time recording, HDMI and VGA output at up to 1920×1080P resolution, Long transmission distance over coax cable, Support up to 16-ch synchronous playback at 1080P resolution

---



**WD10PURX - Purple Edition: Discos especiales para videovigilancia 24/7**

1TB / 64MB (6Gb/s) / IntelliPower (RPM)/SATA

---



**WD20GURX - Purple Edition: Discos especiales para videovigilancia 24/7**

2TB / 64MB (6Gb/s) / IntelliPower (RPM) / SATA

---



**WD30PURX - Purple Edition: Discos especiales para videovigilancia 24/7**

3TB / 64MB (6Gb/s) / IntelliPower (RPM) / SATA

---



**WD40PURX - Purple Edition: Discos especiales para videovigilancia 24/7**

4TB / 64MB (6Gb/s) / IntelliPower (RPM) / SATA

---

**GIMEXPRO**  
**737**



Full HD  
1920x1080

**GIMEXPRO** FULL HD 1080P

### **GIMEXPRO-957 - Cámara y DVR Móvil**

Cámara / DVR Móvil Full HD 1080P, con sensor Ambarella A2S70, con un sensor CMOS de 5 Mega Pixels, Resolución de 1920(H)×1080 (V), 120 grados de apertura, salida HDMI y USB, tarjeta SD y MicroSD clase +10.

---



**GIMEXPRO** 700TVL

### **GIMEXPRO-737 - Cámara y DVR Móvil**

Cámara / DVR Móvil de 700TVL, IR, 140 grados de apertura, salida HDMI y USB, con soporte para tarjeta MicroSD clase +10.

---



**SPECTRUM**  
TECNOLOGIA

Boulevard de Sabana Grande, entre calles Unión y Villaflores  
Torre City Market Bazar, Piso 3. Caracas - Venezuela  
Teléfonos: +58 (212) 761.9990 - 761.2521 - 732.3498  
Email: [contacto@spectrum.com](mailto:contacto@spectrum.com)  
[www.spectrum.com.ve](http://www.spectrum.com.ve)